



Quintolubric® 958-30

Phillips 66® Quintolubric 958-30 is an invert emulsion (water-in-oil) fire-resistant hydraulic fluid designed for use in hydraulic systems operating in areas subject to fire hazards, such as in steel mills, foundries, and mining equipment. It combines the benefits of an oil-based hydraulic fluid with the fire-resistant properties of water. It is approved by the MSHA for use in underground mining equipment.

Quintolubric 958-30 is formulated with ~45% water emulsified with petroleum oil. When exposed to a source of ignition, the oil film may catch fire, but the fire is immediately snuffed out by steam from the water core. A carefully balanced additive package provides enhanced lubricity and excellent emulsion stability, as well as excellent wear protection and corrosion protection for hydraulic system components.

Applications

- Hydraulic systems subject to fire hazards
- Underground mining equipment requiring a fire-resistant, MSHA-approved hydraulic fluid
- Steel mills, foundries, and manufacturing plants

Features/Benefits

- Fire resistant
- Protects against wear
- Protects against rust and corrosion
- Forms a stable emulsion
- Resists bacterial growth
- MSHA approved (Approval Number 30-20-2)

CAUTION: Quintolubric 958-30 should **not** be used in hydraulic systems where operating temperatures exceed 175°F. This product contains water and should not be stored at temperatures over 130°F or below 40°F. Water content should be closely monitored to insure safe operation.

**Invert Emulsion
Type Fire-
Resistant
Hydraulic Fluid;
MSHA Approved**





Quintolubric® 958-30

Typical Properties	
Grade	958-30
Specific Gravity @ 60°F	0.948
Density, lbs/gal @ 60°F	7.90
Appearance, Visual	Opaque White to Tan
Flash Point (COC), °C (°F)	N/A ⁽¹⁾
Pour Point, °C (°F)	-23 (-10)
Viscosity	
cSt @ 50°F	374
cSt @ 100°F	90
Viscosity Index	135
Freeze-Thaw Stability, 10 Cycles, Water Separation, %	None
Water Content, vol %	~45

⁽¹⁾**Note:** This product does not support combustion.

Note: Quintolubric® is a registered trademark of Quaker Chemical Corporation.

Health & Safety Information

For recommendations on safe handling and use of this product, please refer to the Safety Data Sheet via <http://www.phillips66.com/EN/products/Pages/MSDS.aspx>.

07-12-16

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© Phillips 66 Company. Phillips 66® and its respective logos and products are registered trademarks of Phillips 66 Company in the U.S.A. and other countries.